

Product specification – gates

Specyfikacja wyrobu – bramy

 Symbol SC 71 004E
 Edition 01
 Date 01.03.2005
 Page 1 z 1
1. Product name

Swing gates Bekafor Classic type, single and double
Standard types

Single swing gates 1-W	Double Swing gates 2-W
100x103	300x103
100x123	300x123
100x153	300x153
100x173	300x173
100x203	300x203

2. Description

Completely welded construction. Wing frame made out of hollow section profiles. Infills are out of Bekafor Classic welded panels. Wings are cataforetic coated. Posts are pregalvanised Bekaclick profiles. Wings and posts are subsequently polyester coated. Gates are equipped with: adjustable hinges and concealed mortise lock with Euro cylinder. Double gates additionally have groundbolts.

3. Technical data

Dokument drukowany z systemu. Obowiązuje bez podpisu.	Raw material - wings					
			Frame		Infill – Bekafor Classic	
	Dimensions:		section:	40x40 mm	mesh:	50x100 mm
			wall thick. :	1,5 mm	diameter:	3,8 mm
	Material properties:	Rm:	min. 320 N/mm ²		min. 500 N/mm ²	
		Kataforetic coat	20 µm			
	Raw material - posts					
	Section dimensions:		Ø60 mm			
	Wall thickness :		2,0 mm			
	Tensile strength Rm		min. 320 N/mm ²			
	Thickness of zinc		275 g/mm ² (both sides)			
	Gate wing properties					
	Wing diagonals difference:		max. 2 mm / m			
	Wing flatness:		max. 8 mm			
Type of coat		polyester				
Thickness of coat		min 60 µm				
Condition of coat		coat tight and homogenous				
Color of coat		green RAL 6005				

4. Packing

- Gates are delivered on wooden four-way pallets,
- Single gates: 5 per pallet. Double gates: 6 per pallet.
- Gates protected by shrinkfoil and plastic corner protections.
- Every pallet has a label with number of items, SAP number and short description of the gate.

Applies to: Sales		Supervision: KJ	
Date of previous issue:	Worked by : <i>Paweł Spieszko</i>	Approved : <i>Waldemar Mnich</i>	