Dokument drukowany z systemu. Obowiązuje bez podpisu.

1. Product name

Fence panel Bekafor Prestige

Dimensions	Draw. No
2015x886	FP-004-01
2015x1086	FP-004-02
2015x1286	FP-004-03
2015x1486	FP-004-04

2. Description

Welded panel made out from galvanized wires and polyester coated after welding. Dimensions and tolerances according to drawing.

3. Technical data

Wire properties		
	Line wires	Cross wires
Diameter and tolerance	5,0 - 0,20 mm	5,0 + / - 0,20 mm
Tensile strength Rm	min. 500 N/mm^2	min. 500 N/mm^2
Qyantity of zinc	min. 40 g/m^2	min. 40 g/m^2

Panel properties	
Difference in diagonals	max. 4 mm
Flatness	max.15 mm
Weld strength	min. 20 Nm
Condition of surface	wires without scratches and burrs, welds without excessive fash

Powder coating (optional)	
Type of coat	polyester
Thickness of coat	min 100 µm
Condition of coat	coat tight and homogenous
Color of coat	green, RAL 6005 anthracite

4. Packing

- Panels are delivered on wooden four-way pallets,
- 50 panels on pallet,
- Panels protected by biplex sheet and shrinkfoil
- Every pallet has a label stating number of panels, mesh size, width and height of the panel.

This document is the property of BETAFENCE Sp. z o. o.
No part of this document may be copied or transmitted without written permission of General Director