URSUS® AS Medium Trigalv®

1. Wire properties

Parameter	Unit	Selvedge wire	Line wire	Stay wire
Diameter	mm	2,50 ± 0,12	2,00 ± 0,09	1,90 ± 0,09
Tensile strength	N/mm^2	1150 ÷ 1350	1200 ÷ 1400	400 ÷ 550
Min. zinc quantity	g/m^2	245	215	215

2. Mesh dimensions

Distance between selvedge and line wires and length of rolls:

Mesh	Tolerance	Number of meshes				
		200/25/15	200/22/15	200/22/30	200/17/15	200/17/30
50 mm	± 3,0 mm	16	10	10	0	0
100 mm	± 3,0 mm	3	6	6	11	11
150 mm	± 3,0 mm	2	2	2	2	2
200 mm	± 3,0 mm	3	3	3	3	3
Length [m]	- 0 % + 2 %	50	50	100	50	100

Mesh	Tolerance	Number of meshes				
		180/24/15	160/23/15	160/20/15	160/15/15	160/15/30
50 mm	± 3,0 mm	16	16	10	0	0
100 mm	± 3,0 mm	3	3	6	11	11
150 mm	± 3,0 mm	2	2	2	2	2
200 mm	± 3,0 mm	2	1	1	1	1
Length [m]	- 0 % + 2 %	50	50	50	50	100

3. Distance between stay wires: 152,4 ± 3,0 mm or 304,8 ± 3,0 mm

4. Mesh height and tolerance: 2000 ± 6,0 mm or 1800 ± 6,0 mm or 1600 ± 6,0 mm

Dokument drukowany z systemu. Obowiązuje bez podpisu.

This document is the property of BETAFENCE Sp. z o. o.
No part of this document may be copied or transmitted without written permission of General Director